

PS-POU120K3#50BC0KR

Features:

- >> **High reliability design** :- Wide input voltage range 138-485Vac (Phase voltage 80-280Vac), no derating when input voltage \geq 305Vac.
- >> **Parallel redundancy function** :- Support parallel expanded operation: maximum is 6 units. Support sharing batteries for the UPS in parallel.
- >> **Flexible battery configuration** :- Batteries number of each group can be selected from 30pieces to 50 pieces.
- >> **Strong load capacity** :- Output power factor is 1.0, UPS can supply power to 100%unbalance load. High adaptability for load, it can connect full inductive load orcapacitive load.
- >> **LBS function** :- LBS function can realize 2 independent UPS system work in synchronization, and it enhances the reliability of the system.
- >> **Intelligent management** :- Support USB, RS485, RS232, SNMP, dry contact card.



Applications

**FINANCE****Telecom****MEDICAL****INDUSTRIAL**

Technical Specifications

MODEL		PS-POU120K3#50BC0KR
Capacity(VA/Watts)		120k
INPUT		
Nominal voltage		380/400/415Vac (3Ph+N+PE)
Operating voltage range		138~305Vac for 40% load; 305~485Vac for 100% load
Operating frequency range		40~70Hz
Power factor		≥0.99
Harmonic distortion (THDi)		≤3% Linear load
Bypass voltage range		Max.voltage:220V:+25% (Optional+10%,+15%,+20%) 230V:+20% (Optional+10%,+15%) 240V:+15% (Optional+10%) Min.voltage: — 45% (Optional -10%, -15%, -20%, -30%)
Frequency protection range		50/60Hz±10%
Generator input		Support
OUTPUT		
Output voltage		380/400/415Vac (3Ph+N+PE)
Voltage regulation		±1%
Power factor		1.0
Output frequency	Line Mode	Synchronize with input, when the input frequency > ±10% (±1%/±2%/±4%/±5% optional), output 50/60 (±0.1Hz)
	Bat. Mode	
Crest factor		3:1
Harmonic distortion (THDv)		≤2% with linear load; ≤4% with non linear load
Overload	AC Mode	≤110% 60min, ≤125% 10min, ≤150% 1min, > 150% 1.2s shut down inverter
	Bypass Mode	30°C: 135% for long term; 40°C: 125% for long term; > 1000%, 100ms
EFFICIENCY		
Efficiency		up to 95.5%
BATTERY		
Battery voltage		360Vdc ~ 600Vdc
Battery type		VRLA / Li
Charge Current		40A Max.
SYSTEM FEATURES		
Transfer time		Utility to Battery: 0ms; Utility to Bypass: 0ms
Backfeed protection		Support
Alarm		Overload, utility abnormal, UPS fault, battery low, etc
Protection		Short circuit, overload, over temperature, battery low, fan fault alarm
Remote LCD		Support
Communication		USB, RS232, RS485, parallel port, dry contact, intelligent slot, LBS, SNMP card (Optional), relay card (Optional)
ENVIRONMENTAL		
Operating temperature		0°C ~ 40°C
Storage temperature		25°C ~ 55°C (No battery)
Humidity range		0 ~ 95% (Non condensing)
Altitude		< 1000m, derating required when > 1000m
Noise level		< 62dB
PHYSICAL		
Dimension WxDxH (mm)		442 x 850 x 1200
Net weight (kg)		152 kg