

PSiO6KW#550VPVI

Features:

- >> LED display, touch button design, direct data view
- >> Maximum efficiency 97.6%, more power generation
- >> Dual MPPT, support for parallel connection for greater adaptability
- >> 130% DC over configuration, 110% AC overload output; Wide DC voltage range
- >> IP65 protection, built-in SPD protection for safety and reliability
- >> Intelligent remote monitoring
- >> Support anti-backflow function



Technical Specifications

Technical Data	PSiO6KW#550VPVI
Input Data	
Max. PV access power	12000W
Max. PV input power	7800W
Max. PV input voltage	550V
Operation voltage range	80V-540V
Number of independent MPPT/ strings per MPPT	2/1
	20A/20A
AC Output Data	
Rated output power	6 kW
Max. output power	6.6kW
Rated output voltage	230V/ 180V-280V
Rated output frequency	50Hz/60Hz
Rated output current	26.1 A
Max. output current	29A
Power factor	-0.8~+0.8(adjustable)
THDi	<3%(Nominal Output)
Grid system pattern	L+N+PE
Efficiency	
Max. efficiency	97.6%
Europe efficiency	96.8%
Protection	
Input DC switch	Yes
Input over current protection	Yes
DC reverse polarity protection	Yes
Output over voltage protection	Yes
Output over current protection	Yes
Anti islanding protection	Yes
Insulation impedance protection	Yes
RCD detection	Yes
General Data	
Dimensions (L/W/H) in mm	330/188/312
Weight	11.4kg
Noise	<25dB
Operation temperature range	-25°C ~+60°C
Heat dissipation mode	Natural
IP Class	IP65
Maximum altitude	4000m
Self-Consumption night	<1w
Topology	Transformerless
Features	
LCD display	Yes
Communication interface	WIFI/4G/GPRS/RS485(optional)